

**SPEC. NO.:** PS-51695-XXXXX-XXX

**REVISION:** A

**PRODUCT NAME:** 0.5 mm PITCH EASY ON FPC CONN.

SMT R/A B/C TYPE

**PRODUCT NO:** 51695 SERIES

<b>PREPARED:</b>  <b>DATE:</b> <b>2017/07/10</b>	<b>CHECKED:</b>  <b>DATE:</b> <b>2017/07/10</b>	<b>APPROVED:</b>  <b>DATE:</b> <b>2017/07/10</b>
---	--	---

**TITLE: 0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **2** OF **15**

1	REVISION HISTORY .....	3
2	SCOPE.....	4
3	APPLICABLE DOCUMENTS .....	4
4	REQUIREMENTS .....	4
5	PERFORMANCE .....	5
6	INFRARED REFLOW CONDITION.....	8
7	PRODUCT QUALIFICATION AND TEST SEQUENCE.....	9
8	CONNECTOR OPERATION .....	10

TITLE: **0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **3** OF **15****1 Revision History**

<b>Rev.</b>	<b>ECN #</b>	<b>Revision Description</b>	<b>Prepared</b>	<b>Date</b>
O	ECN-1707124	MODIFY ENVIRONMENTAL REQUIREMENT	JAMESLEN	2017.07.10
A	ECN-1708337	ADD Salt Spray Gold plating $\geq 5 \mu$ "	JAMESLEN	2017.08.21

TITLE: **0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **4** OF **15**

## 2 SCOPE

This specification covers performance, tests and quality requirements for **0.5 mm Pitch Easy On FPC CONN. SMT R/A B/C TYPE**.

**ACES Part/Number : 51695 SERIES**

## 3 APPLICABLE DOCUMENTS

EIA-364: ELECTRONICS INDUSTRIES ASSOCIATION

## 4 REQUIREMENTS

### 4.1 Design and Construction

- 4.1.1 Product shall be of design, construction and physical dimensions specified on applicable product drawing.
- 4.1.2 All materials conform to R.o.H.S. and the standard depends on TQ-WI-140101.

### 4.2 Materials and Finish

- 4.2.1 Contact: High performance copper alloy (Phosphor Bronze)  
Finish: (a) Contact Area: Refer to the drawing.  
(b) Under plate: Refer to the drawing.  
(c) Solder area: Refer to the drawing.
- 4.2.2 Housing: Thermoplastic or Thermoplastic High Temp., UL94V-0
- 4.2.3 Actuator: Thermoplastic or Thermoplastic High Temp., UL94V-0
- 4.2.4 Fitting Nail: Copper Alloy, Finish: Refer to the drawing.

### 4.3 Ratings

- 4.3.1 Working voltage less than 36 volts AC (per pin)
- 4.3.2 Voltage: 50 Volts AC (per pin)
- 4.3.3 Current: 0.5 Amperes (per pin)
- 4.3.4 Operating Temperature : -40°C to +85°C

TITLE: **0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **5** OF **15****5 Performance**

## 5.1. Test Requirements and Procedures Summary

<b>Item</b>	<b>Requirement</b>	<b>Standard</b>
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
<b>ELECTRICAL</b>		
<b>Item</b>	<b>Requirement</b>	<b>Standard</b>
Low Level Contact Resistance	100 m $\Omega$ Max. per contact	Mate connectors, measure by dry circuit, 20mV Max., 100mA Max. (EIA-364-23)
Insulation Resistance	1000 M $\Omega$ Min.	Unmated connectors, apply 100 V DC between adjacent terminals. (EIA-364-21)
Dielectric Withstanding Voltage	No discharge, flashover or breakdown. Current leakage: 1 mA max.	200 VAC Min. at sea level for 1 minute. Test between adjacent contacts of unmated connectors. (EIA-364-20)
Temperature rise	30°C Max. Change allowed	Mate connector: measure the temperature rise at rated current until temperature stable. The ambient condition is still air at 25°C (EIA-364-70, METHOD1,CONDITION1)

**TITLE: 0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **6** OF **15****MECHANICAL**

<b>Item</b>	<b>Requirement</b>	<b>Standard</b>
Durability	10 cycles.	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of 25.4 ± 3mm/min. (EIA-364-09)
Terminal /Housing Retention Force	50 gf MIN.	Operation Speed : 25.4 ± 3 mm/minute. Measure the contact retention force with Tensile strength tester.
Fitting Nail /Housing Retention Force	50 gf MIN.	Operation Speed : 25.4 ± 3 mm/minute. Measure the contact retention force with Tensile strength tester.
Vibration	1 µs Max.	The electrical load condition shall be 100 mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency between the limits of 10 and 55 Hz. The entire frequency range, from 10 to 55 Hz and return to 10 Hz, shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. (EIA-364-28 Condition I)
Shock (Mechanical)	1 µs Max.	Subject mated connectors to 50 G's (peak value) half-sine shock pulses of 11 milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. (EIA-364-27, test condition A)

TITLE: **0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A


ECN No: ECN-1708337

PAGE: **7** OF **15****ENVIRONMENTAL**

<b>Item</b>	<b>Requirement</b>	<b>Standard</b>
Resistance to <b>Reflow</b> Soldering Heat	See Product Qualification and Test Sequence Group 10 ( <b>Lead Free</b> )  Appearance: No damage	Pre Heat : 150°C~180°C, 60~120sec. Heat : 230°C Min., 40sec Min. Peak Temp. : 260°C Max, 10sec Max.
Thermal Shock	Appearance :No damage Contact Resistance:100mΩ Max. Insulation Resistance:1000MΩ Min. Dielectric Withstanding Voltage: No breakdown	Mate module and subject to follow condition for 5 cycles. 1 cycles: -55 +0/-3 °C , 30 minutes +85 +3/-0 °C , 30 minutes (EIA-364-32, test condition I)
Humidity	Appearance :No damage Contact Resistance:100mΩ Max. Insulation Resistance:1000MΩ Min. Dielectric Withstanding Voltage: No breakdown	Mated Connector 40°C , 90~95% RH, 96 hours. (EIA-364-31,Condition A, Method II)
Temperature life	Appearance :No damage Contact Resistance:100mΩ Max. Insulation Resistance:1000MΩ Min. Dielectric Withstanding Voltage: No breakdown	Subject mated connectors to temperature life at 85°C for 96 hours. (EIA-364-17, Test condition A)
Salt Spray (Only For Gold Plating)	Appearance :No damage	Subject mated/unmated connectors to 5% salt-solution concentration, 35°C (I) Gold flash for 8 hours (II) Gold plating 3 u" for 48 hours (III) Gold plating $\geq 5$ u" for 96 hours (EIA-364-26)
Solder ability	Tin plating: Solder able area shall have minimum of 95% solder coverage. Gold plating: Solder able area shall have minimum of 75% solder coverage	And then into solder bath, Temperature at 245 $\pm$ 5°C , for 4-5 sec. (EIA-364-52)
Hand Soldering Temperature Resistance	Appearance: No damage	T $\geq$ 350°C , 3sec at least.

**Note.** Flowing Mixed Gas shall be conduct by customer request.

## 6 INFRARED REFLOW CONDITION



TITLE: **0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **9** OF **15****7 PRODUCT QUALIFICATION AND TEST SEQUENCE**

Test or Examination	Test Group										
	1	2	3	4	5	6	7	8	9	10	11
	Test Sequence										
Examination of Product				1、7	1、6	1、4		1		1、4	
Low Level Contact Resistance		1、3	1、4	2、10	2、9	2、5				3	
Insulation Resistance				3、9	3、8						
Dielectric Withstanding Voltage				4、8	4、7						
Temperature rise	1										
Durability		3									
Vibration			2								
Shock (Mechanical)			3								
Thermal Shock				5							
Humidity				6							
Temperature life					5						
Salt Spray(Only For Gold Plating)						3					
Solder ability							1				
Terminal / Housing Retention Force									1		
Fitting Nail /Housing Retention Force											1
Resistance to Soldering Heat										2	
Hand Soldering Temperature Resistance								2			
<b>Sample Size</b>	<b>2</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>2</b>	<b>4</b>	<b>4</b>	<b>4</b>	<b>4</b>

**TITLE: 0.5 PITCH EASY ON FPC TYPE**


RELEASE DATE: 2017/08/21

REVISION: A


ECN No: ECN-1708337

PAGE: **10** OF **15****8 CONNECTOR OPERATION****OPERATION****FPC insertion procedure. Connector installed on the board.**


1) Lift up the actuator. Use thumb or index finger.



2) Fully insert the FPC in the connector parallel to mounting surface, with the exposed conductive traces facing down.



3) Rotate down the actuator until firmly closed. It is critical that the inserted FPC is not moved and remains fully inserted.



**TITLE: 0.5 PITCH EASY ON FPC TYPE**


RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **11** OF **15****FPC/FFC Removal**

- 1) Lift up the actuator.
- 2) Carefully remove the FPC/FFC.

**PRECAUTIONS****PC board flexing**

- 1)SPC board connector mounting area

The connectors are straight within 0.1 mm max.

Make sure that the PC board connector mounting area flatness can accept the connector terminals without causing any failure of the solder joints.

- 2)SHandling before mounting on PCB

Insertion of the FPC or operation of the actuator prior to mounting on the PCB is NOT RECOMMENDED.

- 3)SPC Board handling

Exercise caution when handling boards with the connectors installed. Do not apply any forces affecting soldered joints.

**A. Lock release**

Carefully rotate the actuator up to 90°, lifting it at the center.

- The actuator opens by rotating it in the direction OPPOSITE to the direction of the insertion of the FPC. DO NOT attempt to open it from the same side as the insertion of the FPC.




**TITLE: 0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **12** OF **15**



**TITLE: 0.5 PITCH EASY ON FPC TYPE**


RELEASE DATE: 2017/08/21

REVISION: A


ECN No: ECN-1708337

PAGE: **13** OF **15**


- 1) Do when you pull out mating FPC/FFC with the Actuator opened completely. Confirm whether to Have adhered to the terminal contact part before FPC/FFC is mated with the connector housing when the opening of the actuator is the un-complete and FPC/FFC is pulled out.



- 2) Do not add the load mating FPC/FFC with connector housing.



- 3) Due to the structure of the connectors, they do not have string resistance to upward pulling; therefore, support the FPC/FFC when a pulling force is applied to it.



**TITLE: 0.5 PITCH EASY ON FPC TYPE**

RELEASE DATE: 2017/08/21


REVISION: A

ECN No: ECN-1708337

PAGE: **14** OF **15**

4) This connector is small and thin and requires delicate and careful handling.

Be very careful not to apply any force to the FPC after inserting it.  
Otherwise, the connector may become unlocked or the FPC may break.  
Fix the FPC, in particular, when loads are applied to it continuously.  
Design the FPC layout with care not to bend it sharply near the insertion opening.



**TITLE: 0.5 PITCH EASY ON FPC TYPE**


RELEASE DATE: 2017/08/21

REVISION: A

ECN No: ECN-1708337

PAGE: **15** OF **15**

FPC Bending Direction: UP



FPC Bending Direction: DOWN

